



YPL LEVEL & INSTRUMENTS

FLOW SWITCH DISC: YPL-FSD32

Introduction

YPL online type plug (disc) operated magnetic flow switch are suitable for sensing flow of liquids like oil, chemical or in water lines. These switches can either be supplied in weather proof housing.

Principle of Operation

Change in flow through valve body raises or lowers the plug which causes attraction sleeve to move in the enclosing tube. The increase of flow causes flow plug to lift which causes attraction sleeve to move up in the field of permanent magnet located outside the enclosing tube, which causes the switch to operate. When the flow rate drops below the rate for which flow plug is calibrated, a reversal of this action takes place.

Specification

Service	: condensate, oil, liquids
Process Connection	: screwed NPT or flanged
Sensing Element	: plug
Temperature	: 150°C
Operating Pressure	: Upto 25 kg/cm ²
Enclosure	: Weather proof
Enclosing Tube	: SS316
Attraction sleeve	: SS410
Disc & stem	: SS316
Body	: bronze/SS316
Electric Connection	: ½" NPT
Setting accuracy	: ±25mm



FIG. 1

Flow rates water service

Pipe size	Increasing rate m ³ /hr	Increasing rate m ³ /hr
¾" NPT	0.75	0.55
1" NPT	1.25	1.02
1 ½" NPT	2.75	2.00
2" NPT	3.25	2.75

REGD. OFF: 48/11-B MITHAPUR EXTN. BADARPUR NEW DELHI-110044

Website: www.yplindia.com

Email Id: info@yplindia.com

Ph: 011-26669831